

Technical Information

No. 4187

Edition: 08/05 - subject to change

Substitutes: Edition 01/04

Status: valid

Xenon Short Arc Lamp

XBO[®] 2001 W/HTP OFR

■ Product description

The OSRAM XBO[®] 2001 W/HTP OFR is a DC-operated lamp that is especially suited for applications requiring excellent arc stability and a high luminance. The OSRAM XBO[®] 2001 W/HTP OFR is designed for horizontal burning position (H = horizontal, TP = threaded pin)

■ Technical data

Order reference	XBO [®] 2001 W/HTP OFR	
Rated lamp wattage	W	2000
Rated lamp voltage	V	25
Rated lamp current (=)	A	80
Current control range	A	50 - 85
Ignition voltage	kV _s	33
Min. open circuit voltage for cold / hot ignition	V	85 / 100
Luminous flux	lm	80000
Luminous intensity	cd	7500
Average luminance	cd/cm ²	75000
Luminous area w x h *)	mm	1.3 x 4.0
Electrode gap e (cold)	mm	5.0
Lamp length (overall) L ₁	mm	max. 375
Lamp length L ₂	mm	max. 322
LCL a	mm	142,5
Bulb diameter d	mm	60
Average service life	h	3000
Warranty	h	2400
Base	Cathode: SFc 25-14 Anode: SFa 25-14	

*) w = luminance half width value; h = height of luminance area (corresponds to electrode gap, hot)

■ Lamp operation

Maximum permissible base temperature	°C	230
Cooling		--
Min. air flow velocity around discharge vessel	m/s	7
Magnetic arc stabilization	required in horizontal burning position	
Burning position	s 30 (vertical ± 30° ; anode up) ; p 30 (horizontal ± 30°)	

